



	ODU AMC®	ODU AMC® Easy-Clean	ODU AMC® High-Density	ODU AMC® Threaded	ODU AMC® T□□	ODU AMC® NP
□ □ □ □ □ □	□□IP6K9K	□□IP6K9K	□□IP6K9K	□□IP6K8	□□IP6K8	IP68
□ □ □ □ □ □	IP68	IP6K8	IP68	IP68	IP68	IP68□□□□□□□□□□□□□□□□
□ □	□□□□□	□□□□□	□□□□□	□□□□□	□□□□□	□□□□□
□ □ □ □ □	> 5,000	> 5,000	> 5,000	> 2,000	>500	> 2,000
□ □ □ □ □	□□□PCB	□□□PCB	□□□PCB	□□□PCB	□□□□□□PCB	□□□PCB
□ □ □ □ □	□	□	□□	□	□	□
□ □	□	□	□	□□□□	□□□□	RoHS □□



ODU AMC®

-51°C□+125°C



ODU AMC® Easy-Clean

-51°C□+125°C



ODU AMC® High-Density

-51°C□+125°C



ODU AMC® Threaded

-51°C□+125°C



ODU AMC® T□□

-65°C□+175°C



ODU AMC® NP

-18°C□+71°C

- 
- 
- 
- 
- 
-